



















MFD. BY: EMERGENCY ONE INC.
OCALA, FL. 34474 20502

DATE OF MFR: MO. 08 YR. 99
INC. VEH. MFD. BY: _____

DATE OF INC. VEH. MFR:
MO. 06 YR. 99

GVWR: _____ KG (15,000 LB)

GAWR-FRONT: _____ KG (6,000 LB)

GAWR-REAR: _____ KG (11,000 LB)

CONFORMITY OF THE CHASSIS-CAB TO U.S.A. FEDERAL MOTOR VEHICLE SAFETY STANDARDS, WHICH HAVE BEEN PREVIOUSLY FULLY CERTIFIED BY THE INCOMPLETE VEHICLE MANUFACTURER OR BY THE INTERMEDIATE VEHICLE MANUFACTURER, HAS NOT BEEN AFFECTED BY THE FINAL-STAGE MANUFACTURE. THE VEHICLE HAS BEEN COMPLETED IN ACCORDANCE WITH PRIOR MANUFACTURER'S INSTRUCTIONS, WHERE APPLICABLE. THIS VEHICLE CONFORMS TO ALL OTHER APPLICABLE U.S.A. FEDERAL MOTOR VEHICLE SAFETY STANDARDS IN EFFECT IN:

MO. 08 YR. 99
VEHICLE IDENTIFICATION NUMBER:
1FDXF47F9XEE51905

VEHICLE TYPE:
FIRE APPARATUS

SUITABLE TIRE-RIM CHOICE
FRONT: 225/70R19.5 TIRES, KPA,
19.5X6.00 RIMS, @ _____
(95 PSI) COLD SGL
INTERMEDIATE (1): _____ TIRES, KPA,
RIMS, @ _____
(_____ PSI) COLD _____
INTERMEDIATE (2): _____ TIRES, KPA,
RIMS, @ _____
(_____ PSI) COLD _____
REAR: 225/70R19.5 TIRES, KPA,
19.5X6.00 RIMS, @ _____
(95 PSI) COLD DUAL _____



**INCOMPLETE VEHICLE MANUFACTURED BY
FORD MOTOR COMPANY**

DATE: 05/99

FRONT GAWR: 6000LB

2721KG

225/70R19.5F

19.5X6.0

AT 517 kPa/75

GAWR: 15000LB/6803KG

REAR GAWR: 11000LB

4989KG

225/70R19.5F

19.5X6.0

AT 517 kPa/75

WITH

TIRES

RIMS

PSI COLD

WITH

TIRES

RIMS

PSI COLD

DUAL

VIN: 1FDXF47F9XEE51905



EQUIPPED WITH THE FORD
AMBULANCE PREP. PKG.

EXT	PNT:	F1	WB	BRK	INT	TR	TP/PS	R	AXLE	TR	DSO:	SPR
165	4	V2						7	78	E	XM	

MADE IN U.S.A. UNC F85B-1520472-AB



